



ICP062E - RATIONAL iCombi Pro - Model 6-2/1 - Electric Free-standing Combi Oven - 22.4 kW

The intelligent RATIONAL iCombi Pro 6-2/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- ✔ 6 x GN 2/1 capacity, ideal for restaurants and foodservice applications
- ✔ Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- ✔ iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- ✔ iCookingSuite continuously checks the condition of the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process
- ✔ iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same time
- ✔ iCareSystem - 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- ✔ WiFi interface for connected cooking and easy access to HACCP documentation

Specifications

Summary		Power and Performance	
Brand	Lincat	Total Power kW	22.4
Range	RATIONAL	Temperature Range °C	30-300
Series	iCombi Pro	IP Rating	IPX5
Power Type	Electric	Temperature Control	Electronic
Unit Type	Free-standing	Oven Rating kW	Steam connection = 18.0; Hot air connection = 21.6
Available in UK Only	Yes		
UK Warranty	RATIONAL 2 Years Parts and Labour Warranty		

Key Specifications		Capacity	
WRAS Approved	Yes	Gastronorm Capacity	6 x GN2/1
Type of Lighting	LED	Portions per Day	60-160
Number of Grids included	0		

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	804	Requires Installation	Yes
Unit Width (External) mm	1072	Requires Electrical Supply	Yes
Unit Depth (External) mm	1042	UK 3 Pin Plug	No
Net Weight Kg	137	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	22,400
		Three Phase Amps	L1=35.0; L2=35.0; L3=35.0
		Three Phase Voltage	400
		Water Connection Pressure Bar	6
		Drain Connection	DN 50 mm
		Water Connection	3/4"

Shipping

Packed Weight Kg	150.7
Packed Height cm	96
Packed Width cm	117.5
Packed Depth cm	115.5

Available Accessories

56.00.562	RATIONAL Care Tablets - x 150 [for use with iCC - iCP - SCC - CMP units]
60.31.087	RATIONAL UG II Static Stand for Models 6-2/1, 10-2/1 - 14 Pairs of Support Rails - Side Panels and Top Panel - H 699 mm
60.31.090	RATIONAL UG I Static Stand for Models 6-2/1, 10-2/1 - Open on all Sides - H 699 mm
60.31.092	RATIONAL UG III Static Stand for Models 6-2/1, 10-2/1 - 14 Pairs of Support Rails - Side Panels, Rear Panel and Top Panel- H 699 mm
60.31.094	RATIONAL UG IV Static Stand for Models 6-2/1, 10-2/1 - 14 Pairs of Support Rails - Closed on all Sides, Double Wing Doors - H 699 mm
60.31.102	RATIONAL UG I Mobile Stand for Models 6-2/1, 10-2/1 - Open on all Sides - H 699 mm
60.31.104	RATIONAL UG II Mobile Stand for Models 6-2/1, 10-2/1 - 14 Pairs of Support Rails - Side Panels and Top Panel - H 699 mm
60.31.106	RATIONAL UG III Mobile Stand for Models 6-2/1, 10-2/1 - 14 Pairs of Support Rails - Side Panels, Rear Panel and Top Panel- H 699mm
60.31.108	RATIONAL UG IV Mobile Stand for Models 6-2/1, 10-2/1 - 14 Pairs of Support Rails - Closed on all Sides, Double Wing Doors - H 699 mm
60.31.203	RATIONAL UG I Static Stand for Combi-Duo Models 6-2/1 on 6-2/1 or 10-2/1E - Open on all Sides - H 200 mm
60.31.216	RATIONAL UG III Static Stand for Models 6-2/1 with UltraVent - 20 Pairs of Support Rails - Side Panels, Rear Panel and Top Panel- H 945 mm
60.62.017	RATIONAL Mobile Plate Rack - 34 Plates - Model 6-2/1
60.62.150	RATIONAL Mobile Oven Rack - Model 6-2/1 - 6 Racks - Rail Distance 64 mm - Requires Run-in Rail
60.62.196	RATIONAL Finishing System for Banquets - inc Mobile Plate Rack, Thermocover and Transport Trolley - 34 Plates - Model 6-2/1
60.70.464	RATIONAL Appliance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS
60.70.943	RATIONAL Grill and Pizza Tray - GN1/1(325 x 530 mm)
60.71.157	RATIONAL Multibaker - 8 moulds - GN1/1(325 x 530 mm)
60.71.617	RATIONAL Grilling and Roasting Tray - GN1/1(325 x 530 mm)
60.72.592	RATIONAL Condensation Breaker - Models 6-1/1, 10-1/1, 6-2/1, 10-2/1
60.73.008	RATIONAL VarioSmoker
60.73.999	RATIONAL Transport Trolley for Mobile Oven Racks - Standard - H 990 mm - Model 6-2/1, 10-2/1
60.74.650	RATIONAL Standard Run-in Rail for Mobile Oven Racks - Models 6-2/1, 10-2/1
60.74.725	RATIONAL Combi-Duo Kit - for Models 6-2/1E/G on 6-2/1E or 6-2/1E/G on 10-2/1E
60.75.135	RATIONAL UltraVent® Condensation Hood - for Electric Models 6-2/1, 10-2/1
60.75.143	RATIONAL UltraVent® Plus Smoke and Condensation Hood - for Electric Models 6-2/1, 10-2/1
60.75.605	RATIONAL Transport Trolley for Mobile Oven Racks - Adjustable Height 800-1330 mm - Model 6-2/1, 10-2/1
6004.1016	RATIONAL Thermocover for Mobile Oven Rack and Mobile Plate Rack - Model 6-2/1
6006.0110	RATIONAL Descaler - 10 litres [for iCombi Classic - iCombi Pro - SCC - CMP units]
6010.1101	RATIONAL Rust-free Stainless Steel Grid - GN1/1(325 x 530 mm)
6010.2101	RATIONAL Rust-free Stainless Steel Grid - GN2/1(650 x 530 mm)
6013.1102	RATIONAL Stainless Steel Container - GN1/1(325 x 530 mm) - 20 mm deep
6013.1103	RATIONAL Roasting and Baking Tray - Non-stick - GN1/1(325 x 530 mm)
6013.1106	RATIONAL Stainless Steel Container - GN1/1(325 x 530 mm) - 65 mm deep
6013.2103	RATIONAL Roasting and Baking Tray - Non-stick - GN2/1(650 x 530 mm)
6014.1102	RATIONAL Granite-enamelled Container - GN1/1(325 x 530 mm) - 20 mm deep
6014.1104	RATIONAL Granite-enamelled Container - GN1/1(325 x 530 mm) - 40 mm deep
6014.1106	RATIONAL Granite-enamelled Container - GN1/1(325 x 530 mm) - 60 mm deep
6014.2102	RATIONAL Granite-enamelled Container - GN2/1(650 x 530 mm) - 20 mm deep

Available Accessories

6014.2104	RATIONAL Granite-enamelled Container - GN2/1 (650 x 530 mm) - 40 mm deep
6014.2106	RATIONAL Granite-enamelled Container - GN2/1 (650 x 530 mm) - 60 mm deep
6015.1103	RATIONAL Perforated Baking Tray - GN1/1 (325 x 530 mm)
6015.1165	RATIONAL Stainless Steel Perforated Container - GN1/1 (325 x 530 mm) - 55 mm deep
6015.2103	RATIONAL Perforated Baking Tray - GN2/1 (650 x 530 mm)
6019.1150	RATIONAL CombiFry® Frying Basket - GN1/1 (325 x 530 mm)
6035.1006	RATIONAL Chicken Superspike - 8 Chicken Capacity - GN1/1
6035.1010	RATIONAL Chicken Superspike - 10 Chicken Capacity - GN1/1
6035.1016	RATIONAL Chicken Superspike - 6 Chicken Capacity - GN1/1
6035.1017	RATIONAL CombiGrill Griddle - 1/1 GN (325 x 530 mm)



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm